

Product Code:

2101

HYDRO ISO 32

Industrial hydraulic oil

Meets the requirements:

ISO 32
ISO 11158 (HM)
DIN 51524-2 (HLP)
AFNOR NF E 48-603
CONESTOGA ISO 20763
EATON/SPERRY VICKERS I-286-S
MAG CINCINNATI P-68/P-69/P-70
PARKER (DENISON) HF-0/HF-1/HF-2
DENISON FILTERABILITY TP 02100
US STEEL 126/127

MANNOL Hydro ISO 32 is premium product formulated with an effective anti-wear compound for hydraulic or circulating systems requiring high quality anti-wear oils, such as those recommended by hydraulic pump and machine tool manufacturers. It is formulated with high quality base oils with superior thermal and oxidative stability. Viscosity range: ISO 32.

Product Characteristics:

Test	Method	Unit	Result
Density at 15°C	D 1298	kg/m ³	870
Viscosity at 40°C	D 445	CSt	32,54
Viscosity at 100°C	D 445	CSt	5,40
Viscosity index	D 2270		99
Flash point COC	D 92	°C	208
Pour point	D 97	°C	-38

Volume:

10L	MN2101-10	208L	MN2101-DR
20L	MN2101-20	1000L	MN2101-IBC
60L	MN2101-60		



www.mannol.de

SCT-Vertriebs GmbH
Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

MANNOL®