

Product Code:

2103

HYDRO ISO 68

Industrial hydraulic oil

Meets the requirements:

ISO 68, ISO 11158 (HM), DIN 51524-2 (HLP),
AFNOR NF E 48-603, CONESTOGA ISO 20763,
EATON/SPERRY VICKERS I-286-S,
MAG CINCINNATI P-68/P-69/P-70,
PARKER (DENISON) HF-0/HF-1/HF-2,
DENISON FILTERABILITY TP 02100,
US STEEL 126/127

MANNOL Hydro ISO 68 is a mineral oil, specially designed for use in hydraulic equipment. It meets the requirements of industrial hydraulic systems operating under heavy loads, pressure, temperature or velocity and is recommended for hydraulic systems of the following types: Vickers, Gerotor, Gresen, HPM, Denison, Cessna, Hydreco, Worthington, etc. Also applicable for the lubrication of industrial equipment, transmissions, pneumatic systems etc. Contains anti-wear, antioxidant, anti-corrosion and anti-foam additives. Distinguishes itself with its demulsifying properties, high viscosity, a low pour point and a long lifespan.

Product Characteristics:

Test	Method	Unit	Result
Density at 15°C	D 1298	kg/m ³	890
Viscosity at 40°C	D 445	CSt	72,41
Viscosity at 100°C	D 445	CSt	8,81
Viscosity index	D 2270		93
Flash point COC	D 92	°C	224
Pour point	D 97	°C	-33

Volume:

10L	MN2103-10	208L	MN2103-DR
20L	MN2103-20	1000L	MN2103-IBC
60L	MN2103-60		



www.mannol.de

SCT-Vertriebs GmbH

Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

MANNOL®