

Product Code:

# 2201

# HYDRO HV ISO 32

Industrial hydraulic oil

Meets the requirements:

HV ISO 32 DIN 51 524 p. 2 (HM) DIN 51 524 p. 3 (HV)  
PARKER (formerly DENISON) HF-0/HF-1/HF-2  
EATON M-2950-S and I-286-S3 MAG P68/P69/P70  
ISO 11158 ASTM D6158 SAE MS 1004  
BOSCH REXROTH RE 90220 SEB 181222  
JCMAS P041 HK Hydraulic Specification  
ANSI/AGMA 9005-E02-RO GM LS-2 AIST 126/127

MANNOL Hydro HV series are high performance hydraulic oils blended in combination with hydrotreated base oils to meet the requirements of the most demanding hydraulic systems. MANNOL Hydro HV have been specifically developed to reduce maintenance costs to a minimum and increase productivity by keeping hydraulic systems running efficiently.



Test	Method	Unit	Result
ISO			32
Density at 15°C	D 1298	kg/m <sup>3</sup>	850
Viscosity at 40°C	D 445	CSt	29,20
Viscosity at 100°C	D 445	CSt	6,14
Viscosity index	D 2270		165
Flash point COC	D 92	°C	210
Pour point	D 97	°C	-42

Volume:

10L	MN2201-10	208L	MN2201-DR
20L	MN2201-20	1000L	MN2201-IBC
60L	MN2201-60		

[www.mannol.de](http://www.mannol.de)

SCT-Vertriebs GmbH  
Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

# MANNOL®