

Product Code:

2203

HYDRO HV ISO 68

Industrial hydraulic oil

Meets the requirements:

HV ISO 68 DIN 51 524 p. 2 (HM) DIN 51 524 p. 3 (HV)
PARKER (formerly DENISON) HF-0/HF-1/HF-2
EATON M-2950-S and I-286-S3 MAG P68/P69/P70
ISO 11158 ASTM D6158 SAE MS 1004
BOSCH REXROTH RE 90220 SEB 181222
JCMAS P041 HK Hydraulic Specification
ANSI/AGMA 9005-E02-RO GM LS-2 AIST 126/127

MANNOL Hydro HV series are high performance hydraulic oils blended in combination with hydrotreated base oils to meet the requirements of the most demanding hydraulic systems. MANNOL Hydro HV have been specifically developed to reduce maintenance costs to a minimum and increase productivity by keeping hydraulic systems running efficiently.



Test	Method	Unit	Result
ISO			68
Density at 15°C	D 1298	kg/m ³	878
Viscosity at 40°C	D 445	CSt	61,93
Viscosity at 100°C	D 445	CSt	10,20
Viscosity index	D 2270		152
Flash point COC	D 92	°C	220
Pour point	D 97	°C	-40

Volume:

10L	MN2203-10	208L	MN2203-DR
20L	MN2203-20	1000L	MN2203-IBC
60L	MN2203-60		

www.mannol.de

SCT-Vertriebs GmbH
Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

MANNOL®