

Product Code:

2406

MARINE 3040

Marine oil

Meets the requirements:

SAE 40
API CF-4
TBN 30

MANNOL Marine 3040 is premium, extra high performance 30 TBN engine oil designed for use in the most severe residual-fueled, medium-speed diesel engines used in marine and stationary power applications. These diesel engine oils have been specially formulated to provide outstanding residual fuel compatibility characteristics to deliver excellent engine cleanliness, especially in crankcase, camshaft areas, ring belt and piston undercrowns. They provide excellent high temperature oxidation and thermal stability, low volatility, high load-carrying properties and corrosion protection. MANNOL Marine 3040 have industry-leading thermal and oxidation stability. They have excellent TBN retention and resistance to viscosity increases over long operating periods. They also promote a high level of engine cleanliness with protection against wear.

Product Characteristics:

Test	Method	Unit	Result
Density at 15°C	D 1298	kg/m ³	890
Viscosity at 40°C	D 445	CSt	145
Viscosity at 100°C	D 445	CSt	14,28
Viscosity index	D 2270		95
Flash point COC	D 92	°C	222
Pour point	D 97	°C	-20
TBN	D 2896	gKOG/kg	32

Volume:

208L MN2406-DR 1000L MN2406-IBC



www.mannol.de

SCT-Vertriebs GmbH
Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

MANNOL®