

Product Code:

# 2501

# MULTIFARM STOU

Agricultural machinery oil

Meets the requirements:

SAE 10W-30, API CG-4/CF-4/CF/CE/CD/SF, ACEA E3,  
STOU SPECS: ZF TE-ML 06A/06B (INC. 06R)/06C/07B,  
JOHN DEERE J27, FORD NEW HOLLAND 82009201/-2/-3,  
FORD M2C159B/C, MASSEY FERGUSON M 1139/M 1144,  
UTTO SPECS: API GL-4, ALLISON C-4, CASE I.H. MS 1204/-6/-7/-9,  
MASSEY FERGUSON M 1135/M 1143/M 1145,  
CASE NEW HOLLAND, MAT 3525/3526, FORD M2C86B/C,  
FORD M2C134D, CATERPILLAR TO-2, JOHN DEERE J20C/J20D,  
HYDRAULIC SPECS: SPERRY VICKERS/EATON M2950S/I-286-S,  
SAUER SUNDRAND (DANFOSS) HYDROSTATIC TRANS FLUID,  
WET BRAKE SPECS: SUITABLE FOR WET BRAKES

Product Characteristics:

Test	Method	Unit	Result
SAE-class			10W-30
Density at 15°C	D 1298	kg/m <sup>3</sup>	870
Viscosity at 40°C	D 445	CSt	67,97
Viscosity at 100°C	D 445	CSt	10,83
Viscosity at -25°C	D 5293	CP	4827
Viscosity index	D 2270		150
Flash point COC	D 92	°C	226
Pour point	D 97	°C	-35
TBN	D 2896	gKOH/kg	10,28

Volume:

10L	MN2501-10	208L	MN2501-DR
20L	MN2501-20	1000L	MN2501-IBC
60L	MN2501-60		



[www.mannol.de](http://www.mannol.de)

SCT-Vertriebs GmbH

Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

# MANNOL®