

Product Code:

# 2601

# TO-4 Powertrain

Industrial TDTO®

Meets the requirements:

SAE 10W

CATERPILLAR TO-4

KOMATSU KES 07.868.1

ALLISON C4 (off-road)

MANNOL TO-4 Powertrain Oil is a special gear oil for use in transmission, final drives, hydraulic, brake and other oil-cooled systems in construction, mining and off-road vehicles (tractors, loaders, bulldozers, excavators). Provides a longer life of the clutch discs. Meets the TO-4 requirements for lubricants TDTO® (Transmission/ Drive Train Oil) from Caterpillar. It is not recommended to mix the oil with other hydraulic and/or engine oils.



Test	Method	Unit	Result
SAE-class			10W
Density at 15°C	D 1298	kg/m³	890
Viscosity at 40°C	D 445	CSt	31,79
Viscosity at 100°C	D 445	CSt	5,76
Dynamic Viscosity by Brookfield	D 2983	°C	84582
Viscosity index	D 2270		124
Flash point COC	D 92	°C	216
Pour point	D 97	°C	-34
TBN	D 2896	gKOH/kg	7,86

Volume:

10L	MN2601-10	208L	MN2601-DR
20L	MN2601-20	1000L	MN2601-IBC
60L	MN2601-60		

[www.mannol.de](http://www.mannol.de)

SCT-Vertriebs GmbH

Feldstrasse 154, 22880 Wedel/Hamburg, Germany, [info@sct-germany.de](mailto:info@sct-germany.de), tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

# MANNOL®