

Product Code:

# 2902

# COMPRESSOR OIL ISO 100

## Compressor oil

Meets the requirements:

ISO 100, ISO / DP 6521 (DAA, DAB, DAH, DAG),  
DIN 51 506 (VBL, VCL, VDL), DIN 51 515 p.1/p.2,  
DIN 51 517 p.2, DIN 51 524 p.1/p.2, AFNOR NF E 48-603,  
BSI BS 489, CEGB 207001, MIL-L 17672 D,  
VDMA 24568, BROWN BOVERI HTGD 90117,  
GE GEK 32568 A/C,  
MAG CINCINNATI P-38/P-55/P-54/P-57/P-62,  
MITSUBISHI E00-87182, PARKER DENISON HF-0,  
SIEMENS TLV 9013, US STEEL 120

MANNOL Compressor Oil ISO 100 - Compressor oils  
in accordance with DIN 51.506 and high ageing  
stability. Employment in mobile air compressors and  
single-step stroke and rotary piston compressors,  
screws-, piston and rotary compressors.

Product Characteristics:

Test	Method	Unit	Result
Density at 15°C	D 1298	kg/m <sup>3</sup>	890
Viscosity at 40°C	D 445	CSt	102,04
Viscosity at 100°C	D 445	CSt	11,36
Viscosity index	D 2270		97
Flash point COC	D 92	°C	216
Pour point	D 97	°C	-28

Volume:

1L	MN2902-1	60L	MN2902-60
10L	MN2902-10	208L	MN2902-DR
20L	MN2902-20	1000L	MN2902-IBC



[www.mannol.de](http://www.mannol.de)

SCT-Vertriebs GmbH

Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

# MANNOL®