

Product Code:

4014

AG13+ Antifreeze

Ready-to-use advanced coolant fluid
-40 °C/+125 °C

Meets the requirements:

USA ASTM D3306/D4340/D4985, SAE J1034, BSI UK BS 6580:2010, AFNOR NF R15-601, MB 325.0, BMW/MINI GS 94000, OPEL/VAUXHALL GME L1301, OPEL GM Q1130100, CHRYSLER MS-7170, FORD ESE-M978B4H-A, FORD AF Plus, GM 1825M/1899M, GM SATURN, JAGUAR, JOHN DEERE, MAN 324 Typ NF, DEUTZ DQC CA-14, MTU MTL 5048, NATO S-759

MANNOL AG13+ Advanced Antifreeze -40 °C is a ready-to-serve solution intended for all-the-year-round use in modern radiators. It protects against corrosion and prevents deposits and foam.

Product Characteristics:

Characteristics	Standard	Results
Appearance	-	Yellow
Density at 20°C, kg/l	1,065-1,125	1,097
pH	7-8	7,33
Ethanol content	0%	0%
Freezing point °C	-40	-40
Reserve alkalinity (ml), min	10-15	10,56

Volume:

1L	MN4014-1	60L	MN4014-60
5L	MN4014-5	208L	MN4014-DR
10L	MN4014-10	1000L	MN4014-IBC
20L	MN4014-20		



www.mannol.de

SCT-Vertriebs GmbH
Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

MANNOL®