

Product Code:

4114

AG13+ Advanced

Concentrated advanced coolant fluid

Meets the requirements:

ASTM D3306/D4340/D4985, SAE J1034, NATO S759, MB 325.3, GM 1825M/1899M, GM SATURN, OPEL-GM QL130100, MAN M 324, BMW, JAGUAR, SAAB, ROVER, RENAULT Type D, FORD ESE M978B4H-A, FORD AF Plus, JOHN DEERE, DAF.

MANNOL AG13+ Antifreeze - contains an ingenious inhibitor formulation that efficiently prevents corrosion, depositions and foam formation to guarantee increased service intervals, optimal heat dissipation and overheat protection of your radiator. It is an ethylene glycol based amine-free, nitrite-free, phosphate-free radiator antifreeze with outstanding properties and is therefore suitable for all aluminium, copper and cast iron radiators. Concentrate must be mixed according to the below table and only with water. It is not recommended to mix this product with other antifreeze products.

Water ratio, % (by volume)	Coolant ratio, % (by volume)	Pour point °C
65	35	-20
60	40	-25
55	45	-29
50	50	-38

Volume:

1L	MN4114-1	20L	MN4114-20
5L	MN4114-5	60L	MN4114-60
10L	MN4114-10	208L	MN4114-DR
1000L	MN4114-IBC		



www.mannol.de

SCT-Vertriebs GmbH
Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

MANNOL®