

Product Code:

7114

TS-14 UHPD

Synthetic truck engine oil

Meets the requirements:

SAE 15W-40, ACEA E7, E9, API CJ-4/SN, JASO DH-2, CATERPILLAR ECF-3, CUMMINS CES 20081, DETROIT DIESEL 93K218, DEUTZ DQC III-10 LA, MACK EO-O Premium Plus, MAN 3575, MB 228.31, RENAULT RLD-3, SCANIA Low Ash, VOLVO VDS-4

MANNOL TS-14 UHPD is a synthetic oil designed for use in utility vehicles with diesel engines. It distinguishes itself by extended oil change intervals, a continuous anti-wear protection, less emissions as well as less deposits. Thanks to the unique additive technology this low SAPS oil complies with the specifications ACEA E9, API CJ-4, Mercedes-Benz 228.31 and Volvo VDS-4.

Product Characteristics:

Test	Method	Unit	Result
Density at 15°C	D 1298	kg/m ³	870
Viscosity at 40°C	D 445	CSt	102,20
Viscosity at 100°C	D 445	CSt	14,26
Viscosity at -20°C	D 5293	CP	5250
Viscosity index	D 2270		142
Flash point COC	D 92	°C	226
Pour point	D 97	°C	-40
TBN	D 2896	gKOG/kg	9,82

Volume:

1L	MN7114-1	20L	MN7114-20
5L	MN7114-5	60L	MN7114-60
7L	MN7114-7	208L	MN7114-DR
10L	MN7114-10	1000L	MN7114-IBC



www.mannol.de

SCT-Vertriebs GmbH

Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

MANNOL®