

Product Code:

# 7121

# TS-21 SHPD

Synthetic truck engine oil

Meets the requirements:

SAE 10W-30, ACEA E9-16, API CK-4, JASO DH-2,  
VOVLO-Approval VDS-4,5, MACK-Approval EOS-4.5,  
RENAULT-Approval VI RLD-3, MTU Type 2.1,  
DEUTZ DQC III-18LA, CATERPILLAR ECF-3,  
DETROIT DIESEL DFS 93K222, FORD WSS-M2C171-F1,  
CUMMINS CES 20086, MAN M3775, M3575, MB 228.31

High-performance diesel engine oil, designed for optimum lubrication under heavy operating conditions. The high-quality additive package reduces soot entry and acid-related seal aging due to low diesel quality. Protects against oil thickening, high temperature deposits, sludge formation, oil degradation and corrosion. Excellent low temperature fluidity and high temperature viscosity allow the use in most diesel applications.

Product Characteristics:

Test	Method	Unit	Result
Density at 15°C	D 1298	kg/m <sup>3</sup>	870
Viscosity at 40°C	D 445	CSt	65,41
Viscosity at 100°C	D 445	CSt	11,01
Viscosity at -25°C	D 5293	CP	3114
Viscosity index	D 2270		161
Flash point COC	D 92	°C	230
Pour point	D 97	°C	-40
TBN	D 2896	gKOG/kg	8,85

Volume:

10L	MN7121-10	208L	MN7121-DR
20L	MN7121-20	1000L	MN7121-IBC
60L	MN7121-60		



[www.mannol.de](http://www.mannol.de)

SCT-Vertriebs GmbH

Feldstrasse 154, 22880 Wedel/Hamburg, Germany, [info@sct-germany.de](mailto:info@sct-germany.de), tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

# MANNOL®