

Product Code:

7401

GASOIL

Universal engine oil

Meets the requirements:

SAE 15W-50
API SG/CD

MANNOL Gasoil is an universal motor oil specially manufactured for engines operating with natural gas. Giving high levels of protection against piston ring scuffing, cylinder wear and valve seat wear. Can be used in gasoline and diesel engines.

Product Characteristics:

Test	Method	Unit	Result
Density at 15°C	D 1298	kg/m ³	890
Viscosity at 40°C	D 445	CSt	174,97
Viscosity at 100°C	D 445	CSt	18,18
Viscosity at -20°C	D 5293	CP	6950
Viscosity index	D 2270		115
Flash point COC	D 92	°C	226
Pour point	D 97	°C	-30
TBN	D 2896	gKOG/kg	6,68

Volume:

1L	MN7401-1	20L	MN7401-20
4L	MN7401-4	60L	MN7401-60
5L	MN7401-5	208L	MN7401-DR
10L	MN7401-10	1000L	MN7401-IBC



www.mannol.de

SCT-Vertriebs GmbH
Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

MANNOL®