

Product Code:

7402

DIESEL

Universal engine oil

Meets the requirements:

SAE 15W-40, ACEA E3, A3/B4, API CH-4/SL,
VW-Norm 501 01/505 00, MAN M 3275,
MB 228.3/229.1, MTU DDC Type 2, VOLVO VDS

MANNOL Diesel is a multigrade engine oil with mineral basis for high-augmented diesel engines of passenger cars and trucks with turbocharge. Perfectly balanced additives effectively protect from wear-out and prevent corrosion. Reduces sooting and carbon formation. Provides safe lubrication and engine cleanness at any usage conditions.

Product Characteristics:

Test	Method	Unit	Result
Density at 15°C	D 1298	kg/m ³	890
Viscosity at 40°C	D 445	CSt	93,70
Viscosity at 100°C	D 445	CSt	13,87
Viscosity at -20°C	D 5293	CP	6500
Viscosity index	D 2270		151
Flash point COC	D 92	°C	226
Pour point	D 97	°C	-38
TBN	D 2896	gKOG/kg	9,50

Volume:

1L	MN7402-1	20L	MN7402-20
5L	MN7402-5	60L	MN7402-60
7L	MN7402-7	208L	MN7402-DR
10L	MN7402-10	1000L	MN7402-IBC



www.mannol.de

SCT-Vertriebs GmbH
Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

MANNOL®