

Product Code:

7403

STANDARD

Universal engine oil

Meets the requirements:

SAE 15W-40
API SL/CF

MANNOL Standard 15W-40 is a multipurpose multigrade engine oil with a highly purified mineral basis for highly augmented petrol and diesel engines with and without turbocharger. It has good detergent-dispersing and anti-oxidogenic properties. It contains low-ash additives to prolong the endurance of the catalyst and provides safe engine combustion in tough usage conditions.

Product Characteristics:

Test	Method	Unit	Result
Density at 15°C	D 1298	kg/m ³	890
Viscosity at 40°C	D 445	CSt	95,0
Viscosity at 100°C	D 445	CSt	14,03
Viscosity at -20°C	D 5293	CP	6395
Viscosity index	D 2270		151
Flash point COC	D 92	°C	226
Pour point	D 97	°C	-38
TBN	D 2896	gKOG/kg	10,58

Volume:

1L	MN7403-1	20L	MN7403-20
4L	MN7403-4	60L	MN7403-60
5L	MN7403-5	208L	MN7403-DR
10L	MN7403-10	1000L	MN7403-IBC



www.mannol.de

SCT-Vertriebs GmbH
Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

MANNOL®