

Product Code:

7407

SAE 50

Universal engine oil

Meets the requirements:

SAE 50
API CH-4

MANNOL SAE 50 is a high performance oil suitable for turbo-charged diesel engines or naturally aspirated diesel engines of trucks, construction equipment, fishing boats, locomotives and stationary diesel engines. Also suitable for gear boxes, torque converters and hydraulic systems if the manufacturer requires an engine oil in the appropriate grade for these parts.

Product Characteristics:

Test	Method	Unit	Result
Density at 15°C	D 1298	kg/m ³	890
Viscosity at 40°C	D 445	CSt	213,75
Viscosity at 100°C	D 445	CSt	18,55
Viscosity index	D 2270		96
Flash point COC	D 92	°C	230
Pour point	D 97	°C	-18
TBN	D 2896	gKOG/kg	4,06

Volume:

5L	MN7407-5	60L	MN7407-60
7L	MN7407-7	208L	MN7407-DR
10L	MN7407-10	1000L	MN7407-IBC
20L	MN7407-20		



www.mannol.de

SCT-Vertriebs GmbH
Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

MANNOL®