

Product Code:

7408

SAE 60

Universal engine oil

Meets the requirements:

SAE 60
API CH-4

MANNOL SAE 60 is a high performance oil suitable for turbo-charged diesel engines or naturally aspirated diesel engines of trucks, construction equipment, fishing boats, locomotives and stationary diesel engines. Also suitable for gear boxes, torque converters and hydraulic systems if the manufacturer requires an engine oil in the appropriate grade for these parts.

Product Characteristics:

Test	Method	Unit	Result
Density at 15°C	D 1298	kg/m ³	890
Viscosity at 40°C	D 445	CSt	346,44
Viscosity at 100°C	D 445	CSt	24,99
Viscosity index	D 2270		94
Flash point COC	D 92	°C	230
Pour point	D 97	°C	-18
TBN	D 2896	gKOG/kg	4,15

Volume:

5L	MN7408-5	60L	MN7408-60
7L	MN7408-7	208L	MN7408-DR
10L	MN7408-10	1000L	MN7408-IBC
20L	MN7408-20		



www.mannol.de

SCT-Vertriebs GmbH
Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

MANNOL®