

Product Code:

7506

MOLIBDEN DIESEL

Semi-synthetic engine oil

Meets the requirements:

SAE 10W-40
API CG-4/SL
ACEA A3/B3

MANNOL Molibden Diesel 10W-40 is a multigrade semi-synthetic engine oil for heavy-loaded diesel engines. Effectively reduces the wear-out on all the stages of the engine combustion due to the formation of a unique protective film which endures extreme loads. Prevents formation of steel particles. Has optimal low-temperature characteristics. Effectively reduces sooting and carbon formation.

Product Characteristics:

Test	Method	Unit	Result
SAE-class			10W-40
Density at 15 °C	D 1298	kg/m ³	870
Viscosity at 40 °C	D 445	CSt	98,56
Viscosity at 100 °C	D 445	CSt	14,34
Viscosity at -25 °C	D 5293	CP	6232
Viscosity index	D 2270		149
Flash point COC	D 92	°C	226
Pour point	D 97	°C	-38
TBN	D 2896	gKOH/kg	8,06

Volume:

1L	MN7506-1	60L	MN7506-60
5L	MN7506-5	208L	MN7506-DR
10L	MN7506-10	1000L	MN7506-IBC
20L	MN7506-20		



www.mannol.de

SCT-Vertriebs GmbH
Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

MANNOL®