

Product Code:

# 7508

# GASOIL EXTRA

Semi-synthetic engine oil

Meets the requirements:

SAE 10W-40  
ACEA A3/B3  
API SL/CF  
VW-Norm 501 01/505 00  
MB 229.1

MANNOL Gasoil Extra is a semi-synthetic motor oil specially manufactured for engines operating with natural gas. Giving high levels of protection against piston ring scuffing, cylinder wear and valve seat wear. Can be used in gasoline and diesel engines.

Product Characteristics:

Test	Method	Unit	Result
Density at 15°C	D 1298	kg/m <sup>3</sup>	870
Viscosity at 40°C	D 445	CSt	94,61
Viscosity at 100°C	D 445	CSt	13,96
Viscosity at -25°C	D 5293	CP	6352
Viscosity index	D 2270		150
Flash point COC	D 92	°C	224
Pour point	D 97	°C	-38
TBN	D 2896	gKOG/kg	9,23

Volume:

1L	MN7508-1	60L	MN7508-60
4L	MN7508-4	208L	MN7508-DR
10L	MN7508-10	1000L	MN7508-IBC
20L	MN7508-20		



[www.mannol.de](http://www.mannol.de)

SCT-Vertriebs GmbH  
Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

# MANNOL®