

Product Code:

7808

V-TWIN for Harley Davidson

4-Stroke engine oil

Meets the requirements:

SAE 20W-50
API SM
JASO MA/MA2

Special synthetic four-stroke motorcycle oil designed for Harley-Davidson® with air or liquid cooling systems, with integral or separate transmissions as well as with wet clutches running in oil baths. A modern additive package ensures the stable operation of the lubrication system for heavy-duty engines with a large capacity and an excellent gear shift quality. The exceptionally stable base oil ensures maximum protection against wear and provides perfectly clean engine parts. Meets the requirements of JASO MA2 which provides clarity and smoothness for clutches running in oil baths. Compatible with all exhaust and catalyst systems.

Product Characteristics:

Test	Method	Unit	Result
Density at 15°C	D 1298	kg/m ³	870
Viscosity at 40°C	D 445	CSt	131,76
Viscosity at 100°C	D 445	CSt	17,43
Viscosity index	D 2270		147
Flash point COC	D 92	°C	226
Pour point	D 97	°C	-40
Viscosity at -30°C	D 5293		23200
Viscosity at -20°C	D 5293		6265
Viscosity at -15°C	D 5293		3021
Viscosity at -10°C	D 5293		1790
Noack volatility test	D 5800		5,40

Volume:

10L	MN7808-10	208L	MN7808-DR
20L	MN7808-20	1000L	MN7808-IBC
60L	MN7808-60		



www.mannol.de

SCT-Vertriebs GmbH

Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

MANNOL®