

Product Code:

# 7809

# SCOOTER 4-TAKT

## 4-Stroke engine oil

Meets the requirements:

SAE 10W-40, API SL, JASO MA/MA2,  
HONDA, KAWASAKI, SUZUKI, YAMAHA

Modern semi-synthetic four-stroke engine oil for scooters and other motorcycle types (50-650 cm<sup>3</sup>). Aspects taken into special account during its development were the high demands placed on scooters in daily use with frequent cold starts and high operating temperatures. Provides optimum cold-start characteristics, maximum resistance at high temperatures and maximum shear stability. Ideal for models with injection engines and catalytic converters.

### Product Characteristics:

Test	Method	Unit	Result
Density at 15°C	D 1298	kg/m <sup>3</sup>	870
Viscosity at 40°C	D 445	CSt	84,08
Viscosity at 100°C	D 445	CSt	13,48
Viscosity at -25°C	D 5293	CP	4026
Viscosity index	D 2270		163
Flash point COC	D 92	°C	224
Pour point	D 97	°C	-38
TBN	D 2896	gKOG/kg	6,08

### Volume:

0,5L	MN7809-05	60L	MN7809-60
1L met.	MN7809-1ME	208L	MN7809-DR
10L	MN7809-10	1000L	MN7809-IBC
20L	MN7809-20		



[www.mannol.de](http://www.mannol.de)

SCT-Vertriebs GmbH  
Feldstrasse 154, 22880 Wedel/Hamburg, Germany, [info@sct-germany.de](mailto:info@sct-germany.de), tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

# MANNOL®