

Product Code:

7903

ELITE

Fully synthetic engine oil

Meets the requirements:

SAE 5W-40, API SN/CH-4, ACEA A3/B4,
JASO MA2, MB-Approval 229.5,
PORSCHE A40, VW-Norm 502 00/505 00,
OPEL GM LL-A-025/B-025,
RENAULT RN 0710/0700

MANNOL Elite is a premium full synthetic engine oil of the latest generation, for the lubrication of all 4-stroke gasoline and diesel engines with or without turbo. MANNOL Elite: excellent fluidity at low temperature; very low resistance at start; exceptional viscosity index; very high thermal stability.

Product Characteristics:

Test	Method	Unit	Result
SAE-class			5W-40
Density at 15°C	D 1298	kg/m ³	850
Viscosity at 40°C	D 445	CSt	82,54
Viscosity at 100°C	D 445	CSt	13,61
Viscosity at -30°C	D 5293	CP	6187
Viscosity index	D 2270		169
Flash point COC	D 92	°C	234
Pour point	D 97	°C	-42
TBN	D 2896	gKOH/kg	10,04

Volume:

1L	MN7903-1	10L	MN7903-10
1L met.	MN7903-1ME	20L	MN7903-20
4L	MN7903-4	60L	MN7903-60
4L met.	MN7903-4ME	208L	MN7903-DR
5L	MN7903-5	1000L	MN7903-IBC



www.mannol.de

SCT-Vertriebs GmbH
Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

MANNOL®