

Product Code:

# 7907

# ENERGY COMBI LL

Synthetic longlife engine oil

Meets the requirements:

SAE 5W-30, API SN, ACEA C3,  
VW-Norm 504 00/507 00, VW TL 521 95,  
MB-Approval 229.51, BMW LL-04,  
PORSCHE C30

MANNOL Energy Combi LL is a multigrade synthetic engine oil for modern gasoline and turbo diesel engines with pump-injector units. Provides high pump ability at cold cranking. Has optimal viscosity at wide-ranging temperatures. Effectively prevents from wear-out and provides extreme cleanness of the engine components. Used in the engines with prolonged oil-change interval (LongLife) and without it.

Product Characteristics:

| Test                | Method | Unit              | Result |
|---------------------|--------|-------------------|--------|
| SAE-class           |        |                   | 5W-30  |
| Density at 15 °C    | D 1298 | kg/m <sup>3</sup> | 850    |
| Viscosity at 40 °C  | D 445  | CSt               | 72,59  |
| Viscosity at 100 °C | D 445  | CSt               | 11,86  |
| Viscosity at -30 °C | D 5293 | CP                | 6184   |
| Viscosity index     | D 2270 |                   | 160    |
| Flash point COC     | D 92   | °C                | 224    |
| Pour point          | D 97   | °C                | -48    |
| TBN                 | D 2896 | gKOH/kg           | 8,78   |

Volume:

|     |           |       |            |
|-----|-----------|-------|------------|
| 1L  | MN7907-1  | 20L   | MN7907-20  |
| 4L  | MN7907-4  | 60L   | MN7907-60  |
| 5L  | MN7907-5  | 208L  | MN7907-DR  |
| 10L | MN7907-10 | 1000L | MN7907-IBC |



[www.mannol.de](http://www.mannol.de)

SCT-Vertriebs GmbH  
Feldstrasse 154, 22880 Wedel/Hamburg, Germany, [info@sct-germany.de](mailto:info@sct-germany.de), tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

# MANNOL®