

Product Code:

7909

DIESEL TDI

Synthetic engine oil

Meets the requirements:

SAE 5W-30, API SN/CH-4, ACEA C2/C3,
VW-Norm 505 00/505 01, BMW Longlife-04,
MB 229.51/229.52, GM dexos2, PSA B71 2290

MANNOL Diesel TDI 5W-30 is a high-tech engine oil of high quality for diesel engines of passenger cars with turbocharger as well with or without particulate filter (DPF, FAP). Meets the VW specification 505.01. Reduces wear, especially during the engine starting and warm-up phase. Also suitable for use in petrol engines.

Product Characteristics:

Test	Method	Unit	Result
Density at 15°C	D 1298	kg/m ³	850
Viscosity at 40°C	D 445	CSt	72,93
Viscosity at 100°C	D 445	CSt	12,37
Viscosity at -30°C	D 5293	CP	5482
Viscosity index	D 2270		168
Flash point COC	D 92	°C	224
Pour point	D 97	°C	-42
TBN	D 2896	gKOG/kg	7,90

Volume:

1L	MN7909-1	60L	MN7909-60
5L	MN7909-5	208L	MN7909-DR
10L	MN7909-10	1000L	MN7909-IBC
20L	MN7909-20		



www.mannol.de

SCT-Vertriebs GmbH

Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

MANNOL®