

Product Code:

7915

EXTREME

Synthetic engine oil

Meets the requirements:

SAE 5W-40, API SN/CH-4, ACEA A3/B4, JASO MA2,
MB 229.5, VW-Norm 502 00/505 00,
RENAULT RN 0710/0700

MANNOL Extreme 5W-40 is a multipurpose multigrade engine oil with hydro synthetic basis for modern gasoline and diesel engines with and without turbocharge. Provides high pump ability at cold cranking, providing safe lubrication and wear-out protection. Has optimal viscosity at wide-ranging temperatures. Satisfies the requirements of new engine types with prolonged oil-change interval.

Product Characteristics:

Test	Method	Unit	Result
Density at 15°C	D 1298	kg/m ³	850
Viscosity at 40°C	D 445	CSt	82,38
Viscosity at 100°C	D 445	CSt	13,73
Viscosity at -30°C	D 5293	CP	6251
Viscosity index	D 2270		224
Flash point COC	D 92	°C	224
Pour point	D 97	°C	-38
TBN	D 2896	gKOG/kg	10,13

Volume:

1L	MN7915-1	20L	MN7915-20
4L	MN7915-4	60L	MN7915-60
5L	MN7915-5	208L	MN7915-DR
10L	MN7915-10	1000L	MN7915-IBC



www.mannol.de

SCT-Vertriebs GmbH
Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

MANNOL®