

Product Code:

7918

LEGEND ULTRA

Fully synthetic engine oil

Meets the requirements:

SAE 0W-20, API SN Plus RC, ILSAC GF-5,
MB 229.71, BMW Longlife-17 FE+, GM dexos1 Gen2,
VOLVO VCC RBSO-2AE, OPEL/VAUXHALL 0V0401547,
CHRYSLER, MITSUBISHI, MAZDA, SUZUKI, TOYOTA,
HONDA, SUBARU, NISSAN

MANNOL Legend Ultra is a energy-saving synthetic premium class low viscosity engine oil, specially designed for all year round lubrication of four stroke engines to support exhaust systems' life and efficiency of European and Japanese new generation vehicles with petrol and diesel engines requiring viscosity classes SAE 0W-20.

Product Characteristics:

Test	Method	Unit	Result
Density at 15°C	D 1298	kg/m ³	830
Viscosity at 40°C	D 445	CSt	43,53
Viscosity at 100°C	D 445	CSt	8,20
Viscosity at -35°C	D 5293	CP	5977
Viscosity index	D 2270		166
Flash point COC	D 92	°C	224
Pour point	D 97	°C	-45
TBN	D 2896	gKOG/kg	8,08

Volume:

1L	MN7918-1	20L	MN7918-20
4L	MN7918-4	60L	MN7918-60
5L	MN7918-5	208L	MN7918-DR
10L	MN7918-10	1000L	MN7918-IBC



www.mannol.de

SCT-Vertriebs GmbH

Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

MANNOL®