

Product Code:

8111

TG-1 UNIVERSAL

Truck gear oil

Meets the requirements:

SAE 75W-80, API GL-4,
MAN 341 Type Z4/E3, VOLVO 97307,
ZF TE-ML 01L/02L/16K,
EATON Manual Transmission

Low-friction gear oil that provides protection against wear of heavily loaded transmission elements and gearboxes. Designed for use in synchronized gearboxes of trucks, buses and construction equipment at extremely low temperatures. Extends the oil change intervals thanks to high thermal stability.

Product Characteristics:

Test	Method	Unit	Result
Density at 15°C	D 1298	kg/m ³	850
Viscosity at 40°C	D 445	CSt	45,10
Viscosity at 100°C	D 445	CSt	8,22
Viscosity index	D 2270		159
Flash point COC	D 92	°C	216
Pour point	D 97	°C	-50
Brookfield dynamic viscosity at -40°C	D 2983		130 500

Volume:

10L	MN8111-10	208L	MN8111-DR
20L	MN8111-20	1000L	MN8111-IBC
60L	MN8111-60		



www.mannol.de

SCT-Vertriebs GmbH
Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

MANNOL®