

Product Code:

8112

TG-2 HYPOID

Truck gear oil

Meets the requirements:

SAE 75W-90, J2360, API GL-4/GL-5, API MT-1,
MIL-L 2105 D/PRF 2105 E, EATON Europe,
MAN 341 Type Z2/S1, MB 235.8, MERITOR O-76-N,
SCANIA STO 1:0, VOLVO 97312,
ZF TE-ML 02B/05A/12L/12N/16F/17B/19C/21A

Universal gear oil for high-loaded transmissions, manufactured on the basis of high-quality synthetic base oils with a special set of additives and inhibitors that ensure smooth transmission operation. Suitable for use in synchronised, non-synchronised gearboxes and transfer cases where API GL-5 and GL-4 oils are required.

Product Characteristics:

Test	Method	Unit	Result
Density at 15°C	D 1298	kg/m ³	890
Viscosity at 40°C	D 445	CSt	98,58
Viscosity at 100°C	D 445	CSt	17,41
Viscosity index	D 2270		194
Flash point COC	D 92	°C	216
Pour point	D 97	°C	-46
Brookfield dynamic viscosity at -40°C	D 2983		135 000

Volume:

10L	MN8112-10	208L	MN8112-DR
20L	MN8112-20	1000L	MN8112-IBC
60L	MN8112-60		



www.mannol.de

SCT-Vertriebs GmbH
Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

MANNOL®