

Product Code:

# 8113

# SAE 90

Universal gear oil

Meets the requirements:

SAE 90  
API GL-1

A mineral simple-composition gear oil for mild operating conditions (low loads and sliding velocities). It may be recommended for the lubrication of accessory equipment to be installed in special vehicles (reducers in autocranes, mechanisms of garbage trucks, side lifting components, etc.) when operating at temperatures no lower than  $-18^{\circ}\text{C}$ .

Product Characteristics:

Test	Method	Unit	Result
Density at $15^{\circ}\text{C}$	D 1298	$\text{kg/m}^3$	930
Viscosity at $40^{\circ}\text{C}$	D 445	CSt	201,62
Viscosity at $100^{\circ}\text{C}$	D 445	CSt	14,39
Viscosity index	D 2270		55
Flash point COC	D 92	$^{\circ}\text{C}$	230
Pour point	D 97	$^{\circ}\text{C}$	-22

Volume:

4L	MN8113-4	208L	MN8113-DR
20L	MN8113-20	1000L	MN8113-IBC
60L	MN8113-60		



[www.mannol.de](http://www.mannol.de)

SCT-Vertriebs GmbH  
Feldstrasse 154, 22880 Wedel/Hamburg, Germany, [info@sct-germany.de](mailto:info@sct-germany.de), tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

# MANNOL®