

Product Code:

# 8206

# DEXRON III AUTOMATIC PLUS

Automatic transmission fluid

Meets the requirements:

GM Dexron® III H/G,F  
FORD Mercon® V, FORD M2C138-CJ/M2C166-H  
ZF TE-ML 09/11/14  
ALLISON C4  
CATERPILLAR TO-2  
MB 236.1  
VOITH H 55.6335.xx (G607)

MANNOL Dexron III Automatic Plus is an oil with a high viscosity index for automatic transmissions. It can be used in automatic transmissions, torque convertors, power steering and hydraulic circuits, for which the constructors prescribe a product, which meets the General Motors ATF Type Dexron III or Dexron II-E and Ford Mercon requirements.

Product Characteristics:

Test	Method	Unit	Result
Density at 15°C	D 1298	kg/m <sup>3</sup>	850
Viscosity at 40°C	D 445	CSt	36,27
Viscosity at 100°C	D 445	CSt	7,28
Viscosity index	D 2270		171
Flash point COC	D 92	°C	216
Pour point	D 97	°C	-46
Brookfield dynamic viscosity at -40°C	D 2983		18 000

Volume:

1L	MN8206-1	20L	MN8206-20
1L met.	MN8206-1ME	60L	MN8206-60
4L	MN8206-4	208L	MN8206-DR
4L met.	MN8206-4ME	1000L	MN8206-IBC
10L	MN8206-10		



[www.mannol.de](http://www.mannol.de)

SCT-Vertriebs GmbH  
Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

# MANNOL®