

Product Code:

8301

LHM+ FLUID

Hydraulic fluid

Meets the requirements:

ISO 7308
DIN 51524.3
FIAT 9.55597
IVECO 18-1823
NEW HOLLAND NH-610A
PSA B71 2710
SDFG OF1611S

MANNOL LHM+ Fluid is a hydraulic thin fluid for hydro-pneumatic suspensions systems, brakes, and steering boosters in Citroën, Peugeot, Mercedes Benz and Volkswagen cars. Provide safe and smooth fluid power system functioning at low temperatures (-50 °C). Has high anti wear-out, antioxygenic and anti-corrosion properties. Is neutral to rubber sleeves and seals. Has perfect demulsifying properties.

Product Characteristics:

Test	Method	Unit	Result
Density at 15°C	D 1298	kg/m ³	840
Viscosity at 40°C	D 445	CSt	18,02
Viscosity at 100°C	D 445	CSt	5,87
Viscosity index	D 2270		316
Flash point COC	D 92	°C	216
Pour point	D 97	°C	-53

Volume:

1L	MN8301-1	60L	MN8301-60
10L	MN8301-10	208L	MN8301-DR
20L	MN8301-20	1000L	MN8301-IBC



www.mannol.de

SCT-Vertriebs GmbH
Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

MANNOL®