

Product Code:

1101

KETTENOEL

Chainsaw oil

Meets the requirements:

ISO 100

MANNOL Kettenoel is highly refined oil on a mineral base, designed for lubrication of the cutting chain saws. The oil has high adhesion properties, which ensures good adhesion of oil to the chain during operation. High anti-wear and lubricity characteristics extend the life of the chain. Greasing of the chain can be made both directly by immersing it in a container with the oil, and by an automatic oil supply. Ensures reliable lubrication up to -15 °C. Designed for the lubrication of chains of both petrol and electric saws.

Product Characteristics:

Test	Method	Unit	Result
Density at 15°C	D 1298	kg/m ³	922
Viscosity at 40°C	D 445	CSt	68,3
Viscosity at 100°C	D 445	CSt	14,3
Viscosity index	D 2270		96
Flash point COC	D 92	°C	230
Pour point	D 97	°C	-25

Volume:

1L	MN1101-1	60L	MN1101-60
4L	MN1101-4	208L	MN1101-DR
10L	MN1101-10	1000L	MN1101-IBC
20L	MN1101-20		



www.mannol.de

SCT-Vertriebs GmbH

Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

MANNOL®