

Product Code:

7106

TS-6

UHPD Eco

Synthetic truck engine oil

Meets the requirements:

SAE 10W-40 ACEA E4/E7 API CI-4/SL
GLOBAL DHD-1 MB-Approval 228.5 VOLVO VDS 3
MAN M 3277/M 3377 MTU DDC Type 3 CUMMINS CES 20078
RENAULT RXD/RLD-2 DEUTZ IV-10 MACK EO-N/OE-M Plus
DETROIT DIESEL PGOS 93K215

MANNOL TS-6 UHPD Eco is a synthetic-based Ultra High Performance Diesel (UHPD) engine oil that satisfies the strictest standards of truck producers. Thanks to its unique consistence it has perfect viscosity-temperature properties that guarantee easy cranking at extremely low temperatures and safe protection from wear out at high loads and temperatures. Effectively reduces frictional heating. Significantly prolongs the interval between oil changes (according to the producer's instructions). Has good detergent and dispersive properties providing perfect cleanness of the engine components. Provides efficient engine combustion.

Product Characteristics:

Test	Method	Unit	Result
SAE-class			10W-40
Density at 15°C	D 1298	kg/m ³	870
Viscosity at 40°C	D 445	CSt	85,20
Viscosity at 100°C	D 445	CSt	13,02
Viscosity at -25°C	D 5293	CP	6800
Viscosity index	D 2270		153
Flash point COC	D 92	°C	224
Pour point	D 97	°C	-46
TBN	D 2896	gKOH/kg	12,76

Volume:

10L	MN7106-10	208L	MN7106-DR
20L	MN7106-20	1000L	MN7106-IBC
60L	MN7106-60		



www.mannol.de

SCT-Vertriebs GmbH
Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

MANNOL®