

Product Code:

7405

UNIVERSAL

Universal engine oil

Meets the requirements:

SAE 15W-40
API SG/CD

MANNOL Universal 15W-40 is a multipurpose multigrade engine oil with highly purified mineral basis for modern gasoline and diesel engines. Has good detergent-dispersing properties. Provides safe lubrication and cleanness of the engine components.

Product Characteristics:

| Test | Method | Unit | Result |
|--------------------|--------|-------------------|--------|
| Density at 15°C | D 1298 | kg/m ³ | 890 |
| Viscosity at 40°C | D 445 | CSt | 106,75 |
| Viscosity at 100°C | D 445 | CSt | 13,82 |
| Viscosity at -20°C | D 5293 | CP | 6681 |
| Viscosity index | D 2270 | | 129 |
| Flash point COC | D 92 | °C | 228 |
| Pour point | D 97 | °C | -28 |
| TBN | D 2896 | gKOG/kg | 4,98 |

Volume:

| | | | |
|-----|-----------|-------|------------|
| 1L | MN7405-1 | 20L | MN7405-20 |
| 3L | MN7405-3 | 60L | MN7405-60 |
| 4L | MN7405-4 | 208L | MN7405-DR |
| 5L | MN7405-5 | 1000L | MN7405-IBC |
| 10L | MN7405-10 | | |



www.mannol.de

SCT-Vertriebs GmbH
Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

MANNOL®