

Product Code:

7406

TRAKTOR SUPEROIL

Tractor engine oil

Meets the requirements:

SAE 15W-40
API SG/CD

MANNOL Traktor Superoil is an all year round engine oil that ensures good lubrication of four-stroke diesel engines. It is used in engines of machinery, vehicles and other equipment that requires the use of oil according to the indicated parameters. The oil is recommended for engines with and without turbocharger.

Product Characteristics:

Test	Method	Unit	Result
Density at 15°C	D 1298	kg/m ³	890
Viscosity at 40°C	D 445	CSt	107,26
Viscosity at 100°C	D 445	CSt	13,86
Viscosity at -20°C	D 5293	CP	6556
Viscosity index	D 2270		130
Flash point COC	D 92	°C	226
Pour point	D 97	°C	-28
TBN	D 2896	gKOG/kg	4,98

Volume:

5L	MN7406-5	60L	MN7406-60
10L	MN7406-10	208L	MN7406-DR
20L	MN7406-20	1000L	MN7406-IBC



www.mannol.de

SCT-Vertriebs GmbH
Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

MANNOL®