

Product Code:

8106

HYPROID GETRIEBEOEL

Universal gear oil

Meets the requirements:

SAE 80W-90
API GL-4/GL-5 LS
MIL-L 2105 D
MACK GO-J
MAN 342

MANNOL Hypoid 80W-90 GL-5 is a multigrade high quality transmission oil with mineral basis for high loaded hypoid gearings. Endures extreme loads. Can be used for the lubrication of cone-, cylinder shaped and screw-gears.

Product Characteristics:

Test	Method	Unit	Result
Density at 15°C	D 1298	kg/m ³	890
Viscosity at 40°C	D 445	CSt	190,54
Viscosity at 100°C	D 445	CSt	18,01
Viscosity index	D 2270		103
Flash point COC	D 92	°C	220
Pour point	D 97	°C	-30
Brookfield dynamic viscosity at -40°C	D 2983		145 000

Volume:

1L	MN8106-1	60L	MN8106-60
4L	MN8106-4	208L	MN8106-DR
10L	MN8106-10	1000L	MN8106-IBC
20L	MN8106-20		



www.mannol.de

SCT-Vertriebs GmbH
Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

MANNOL®