

Product Code:

8109

UNIGEAR

Synthetic engine oil

Meets the requirements:

SAE 75W-80
API GL-4/GL-5
MIL-L 2105 C
FORD WSD-M2C200-C
MACK GO-J Plus
PSA B71 2330

High-quality transmission oil based on synthetic base oils. Enables easy and exact shifting even at low temperatures. Please follow the vehicle or aggregate manufacturer's instructions.

Product Characteristics:

Test	Method	Unit	Result
Density at 15°C	D 1298	kg/m ³	850
Viscosity at 40°C	D 445	CSt	45,10
Viscosity at 100°C	D 445	CSt	8,22
Viscosity index	D 2270		159
Flash point COC	D 92	°C	216
Pour point	D 97	°C	-50
Brookfield dynamic viscosity at -40°C	D 2983		145 000

Volume:

1L	MN8109-1	60L	MN8109-60
10L	MN8109-10	208L	MN8109-DR
20L	MN8109-20	1000L	MN8109-IBC



www.mannol.de

SCT-Vertriebs GmbH
Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

MANNOL®