

Product Code:

# 7701

# O.E.M.

## Fully synthetic engine oil

Meets the requirements:

SAE 5W-30, API SN, ACEA C2/C3, GM dexos2, CHEVROLET, OPEL

MANNOL 7701 O.E.M. is energy saving fully synthetic motor oil specially designed to be used in modern petrol and diesel engines for Opel, Chevrolet, Daewoo, GM and Saab. A low ash level additive (MID SAPS) ensures reliable operation of the diesel particulate filter (DPF) and catalytic converters of gasoline engines (CAT). Effectively protects against wear and provide an exceptional clarity of details. Recommended for engines that meets GM dexos2 and earlier specifications of GM LL A025/B025 oil standard. Designed to meet the requirements for operations in hard conditions and long maintenance intervals.

### Product Characteristics:

Test	Method	Unit	Result
Density at 15°C	D 1298	kg/m <sup>3</sup>	850
Viscosity at 40°C	D 445	CSt	64,89
Viscosity at 100°C	D 445	CSt	11,22
Viscosity at -30°C	D 5293	CP	4653
Viscosity index	D 2270		167
Flash point COC	D 92	°C	222
Pour point	D 97	°C	-42
TBN	D 2896	gKOG/kg	8,09

### Volume:

1L	MN7701-1	20L	MN7701-20
1L met.	MN7701-1ME	60L	MN7701-60
4L	MN7701-4	208L	MN7701-DR
4L met.	MN7701-4ME	1000L	MN7701-IBC
10L	MN7701-10		



[www.mannol.de](http://www.mannol.de)

SCT-Vertriebs GmbH

Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

# MANNOL®